



Monocular microscope, 400x,
achromatic objectives

Observation Method - Transmitted Light	Brightfield	Yes
Main Body	Type	Upright
	Construction material	Aluminum die-cast
	Trasportation handle	Yes
Head	Type	Monocular
	Inclination	45°
	360° rotating	Yes
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	23
Eyepieces	Field number (mm)	18
	Magnification	10x
	Pointer	As optional
	Micrometric scale	As optional
Nosepiece	Positions	Triple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS
Objectives	Optical system	160
	Anti-fungus treatment	Yes
	Parfocal distance (mm)	35
	Standard magnifications	40x-400x
	Type	Achromatic
		4x/0.10, W.D. 10.6 mm
		10x/0.25, W.D. 7.0 mm
Stage		40x/0.65, W.D. 0.5 mm
	Type	Round
	Rotation	360°
	Dimensions (mm)	90
	Material	Anti-scratch painting
	Specimen clips	Yes
Condenser - Single Position	Slide number	1
	Type	Diffusing filter with rotating diaphragm wheel
Focusing System	Type	Separated coarse & fine
	Coarse total travel (mm)	18
	Fine total travel (per single rotation) (mm)	0.1
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes

Transmitted Illumination	Type	LED
	X-LED type	No
	Light source power (W)	0.3
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	1
Power Supply for Transmitted Illumination	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 500 mA
	Rechargeable batteries	Yes
	Battery type	Ni-MH (3x, AAA size)
	Working time of batteries (hours)	8
	Charging time of batteries (hours)	8
Accessories Included	Dust cover	Yes
	Tension adjustment tool	Yes
	User Manual	Digital version (downloadable)
Product Dimensions	Height (mm)	322
	Width (mm)	140
	Depth (mm)	182
Product Weight	(kg)	1.7